




COMO+

STONE POLYMER COMPOSITE

TECHNICAL DATA SHEET



Bella Flooring
GROUP

COMO+

STONE POLYMER COMPOSITE

TECHNICAL DATA SHEET

Bella Flooring GROUP

PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Como+
Construction	Stone Polymer Composite
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	5.5mm (0.2165")
Wear Layer	22mil (0.55mm)
Underlayment	1.5mm IXPE (0.0591")
Edge Profile	Micro Bevel
Surface Finish	UV/Ceramic Bead + BellaSure
Embossing	Photo Match Embossing
Edge Profile	Easy-to-install with I4F Drop Lock Technology
Size	9" W x 60" L (230x1515mm)
SQ. Feet Per Carton	22.50 SQFT/CTN
Pieces Per Carton	6 PIECES/CTN
Weight Per Carton	39.5 LBS/CTN
Carton Per Pallet	60 CTNS/PLT
Installation Method	Floating / Glue Down



TECHNICAL PROPERTIES



Dimensional Stability	ASTM F2199 Passes $\leq 0.2\%$ / lineal ft. (305 mm)
Curling	ISO 23999 Passes $\leq 2\text{mm}$
Static Load	ASTM F970 Passes $\leq 0.005\text{"}$ (0.13mm) (without underlayer)
Static Load Limit	SIM Test Passes 1000 psi (0.02mm) (without underlayer)
Residual Indentation	ASTM F1914 Passes Average: $\geq 0.007\text{"}$ (0.18mm) (without underlayer)
Resistance to Chemicals	ASTM F925 Passes No more than a slight change in surface
Resistance to Heat	ASTM F1514 Passes Average $\Delta E < 8.0$
Resistance to Light	ASTM F1515 Passes Average $\Delta E < 8.0$
Critical Radiant Flux	ASTM E648 Passes Class I: $\geq 0.45 \text{ W/Sq.cm}$
Smoke Density	ASTM E662 Passes Flaming & Non Flaming ≤ 450
VOCs/TVOCs, Formaldehyde	CDPH/EHLB Method v1.2 Compliant V1.2-2017
Substances of Very High Concern	REACH SVHC 191 Passes Per Substance: $\leq 0.1\%$ w/w
Heavy Metals	ASTM F963 Passes
Phthalates	ASTM D7823 Passes CPSC-CH-C1001-9.3
Slip Resistance	ASTM D2047 Passes Dry: 0.38 Wet: 0.90
Fungi Resistance	ASTM G21-15 Passes
IIC Rating	ASTM E492 & ASTM E989 Result: 70
STC Rating	ASTM E90 & ASTM E413 Result: 67

SUSTAINABILITY & WARRANTIES



Material Certification	Virgin Vinyl
Environmental Product Declaration	Floor Score® Certified
Health Product Declaration	EPD Vinyl Click
	HPD 2.1 Vinyl Click - 1000 ppm
Warranties	Lifetime Residential & 20-Year Commercial





Bella Flooring GROUP

100% WATERPROOF

COMO +

EASY INSTALL

STONE POLYMER COMPOSITE LUXURY FLOORING



GRIGIO



THREE UNIQUE COLORS AVAILABLE



DA VINCI



MARONNE



GRIGIO

DIMENSIONS	9" X 60"
TOTAL THICKNESS	5.5 MM
WEAR LAYER	22 MIL / .55 MM
EDGE PROFILE	MICROBEVEL
ATTACHED PAD	1.5 MM IXPE
SQUARE FEET PER CARTON	22.50
CARTONS PER PALLET	60
SQUARE FEET PER PALLET	1,350.26
LOCKING SYSTEM	14F DROP LOCK

CORRESPONDING TRANSITIONS

Add a touch of finished perfection to every installation with exact color matched transitions.




END CAP



T-MOULDING



REDUCER



FLUSH
STAIR NOSE

**NEED
ADDITIONAL
DETAILS?**

Scan this QR code with your smart device's camera to visit this product's page on our website.

